PROJECT	QUANTITY	ITEM NO

# Multi-Purpose Holding Cabinet Dual access

The MPC 21L is a compact, modular single-drawer unit that can be placed on countertops, side-by-side or stacked. Each module represents a

separately controlled holding environment that can be accessed at either end. Flexibility improves workflow by making popular menu items instantly accessible wherever they are needed.

Deep drawer pan is sized for a variety of menu items. Easy-grip handle on each end offers convenient access from both sides of unit. One-piece molded construction stands up to the toughest commercial kitchen treatment.

### **Standard Features**

- Space saving design maximizes holding capacity in minimal space
- Drawer pan can be inserted at either end for added flexibility
- Modular design—units can be stacked or placed side-by-side
- Multiple units offer separate, individually controlled holding environments
- · Double-handled drawer pan of heavy duty one-piece molded hightemperature thermoplastic
- Programmable controls with digital temperature display
- Power-on indicator turns green when system is normal and ready
- Modular control system for ease of service
- Welded stainless steel construction for easy-cleaning and long life

MPC 21L dual access modular multi-purpose holding cabinet

7.63 in (195 mm)

8.75 in (222 mm)

(195 mm)

(400 mm)

(610 mm)

(280 mm)

(280 mm)

 $(0.05 \text{ m}^3)$ 

2 in (51 mm) for power cord exit

(11 kg)

7.63 in

15.75 in

24 in

11 in

11 in

25 lb

1.7 ft<sup>3</sup>

Power cord

**Bidding specifications** 

Holding Cabinet with two-sided access for holding environments.

Unit shall incorporate:

- Single drawer capacity with drawer pan access from two sides
- 1 double-handled drawer pan of of heavy-duty
- High-quality stainless steel construction
- Programmable electronic temperature controls

## Heating 140-270°F (60-132°C)

**Required clearances** 

### Pan capacity

Dimensions

Height

Width

Depth

Crated

Length

Depth

Height

Volume

Weight

Side

1 double-handled deep drawer pan

## Electrical

Volts	Phase	Hertz	kW	Amps	Wire*	Cord & Plug Not available for all destinations	Laboratory certifications
120	1	60	0.11	0.92	2+G	Please contact	c 🖤 us 📡 🤇 🧲
230	1	50	0.11	0.47	1NG	Henny Penny	

\*Units shipped without power cord and plug must have power cord and plug installed on site by a qualified electrician.

Continuing product improvement may subject specifications to change without notice.

	APPROVED AS NOTED	
AUTHORIZED SIGNAT	DATE	

© 2014 Henny Penny Corporation, Eaton, OH 45320 USA Revised 09292018

Henny Penny Corporation PO Box 60 Eaton OH 45320 USA

+1 937 456.8400 800 417.8417 +1 937 456.8434 Fax 800 417.8434 Fax +1 800 417.8405 Technical Support



D 15.75 in (400 mm)

packing.

Provide Henny Penny MPC 21L Multi-Purpose hot foods at safe temperatures in separate

- one-piece molded thermoplastic
- with digital temperature display



8.75 in

(222 mm)

MPC 21L Single module